



100W DIMMABLE DALI POWER SUPPLY SINGLE OUTPUT

SIZE:
L:230mm
W:50mm
H:30mm



- AC input: 176-264V
- Protection: short-circuit, overload, over voltage, over temperature
- 100% full-load aging test
- 300VAC surge for 5 seconds withstandable
- Working temperature up to 60°C
- 5G vibration tested
- High efficiency, long life span, and high reliability, low cost
- IP20 grade
- 3 years warranty
- 0-10V dimmable dali

Application

- *Industrial automation machinery
- *industrial control system
- *LED lighting
- *Mechanical and electrical equipment
- *Electronic instruments, equipments or apparatus



Specifications

Product No.		DM-100-12	DM-100-24
Output	DC voltage	12V	24V
	Rated Current	8.3A	4.17A
	Current Range	0-8.3A	0-4.17A
	Rated Power	100W	100W
	Ripple and Noise(Max)Note.2	150mVp-p	240mVp-p
	Voltage adjustment	10.8-13.2V	22-27.6V
	Voltage Accuracy Note3	±1%	±1%
	Linear Adjustment Note4	±0.5%	±0.5%
	Load Adjustment Note5	±0.5%	±0.5%
	Start and rise time		
Hold time (Typ)			
Input	Voltage range		
	Frequency range		
	Efficiency (Typ)	80%	82%
	AC current (Typ)		
	Surge current (Typ)		
	Current leak		
Protection	Overload	Larger than 105% of capacity restoration after abnormality removed	
	Overvoltage		
	Overheat		
Environment	Working temp.	-20~+60°C (Refer to the tenuation curve)	
	Working humidity	20~90% RH, without condense	
	Storage temp & hmdty	-40~+80°C	
	Temp. coefficient	±0.03%/°C (0~50°C)	
	Vibration proof	10~500HZ,5G 10min / cycle, X、Y、Z axes 60 min each	
Safety reg. & EMC (Note.6)	Safety regulation	GB195110.1-2004/IEC61347-1:2003 CE(EMC+LVD)	
	Voltage proof	I/P-O/P:1.5KVAC	
	insulation resistance	I/P-O/P:100M Ohms/500VDC/25°C/70% RH	
	EMC irradiation	EN 55015:2006;EN61000-3-2:1995+A2:2005	
	EMC disturbance proof	EN 61000-3-2:2006;	
Dimensions	230*50*30mm(L*W*H)		
Packing	0.31kg/PCS		
Notes:	1. Unless specially indicated, all data are taken under 230VAC input, rated load and 25°C environment temp.		
	2.Ripple and noise: measured with a 12" double ripple cord connected in parallel with a 0.1µF and a 47 µF capacitor on 20MHz bandwidth.		
	3.Accuracy: including preset errors, linear adjustment rate and load adjustment rate.		
	4.Linear adjustment: taken under rated load from low voltage to high voltage.		
	5.Load adjustment: taken under 0~100% of rated load.		
	6. Power supply is taken as part of the whole system, and needs to be confirmed with terminal instruments for EMC.		